

## DUCTED A/C UNITS





## Features

Wired Controller

Independent Dehumidification

Auto Restart Function

Auto Defrosting

Timer

Sleep Mode

Two Drainage Way

Anti-cold Air Function



GEO ELECTRICAL CONTRACTING TRADING CO. L.L.C

www.geogroupglobal.com

## DUCTED SPLIT A/C UNITS Technical Specifications



|                                      | Indoor Model         |         | GTBT-24                                 | GTBT-36              | GTBT-48              | GTBT-60              |
|--------------------------------------|----------------------|---------|---|----------------------|----------------------|----------------------|
|                                      | Outdoor Model        |         | GTBT-24                                 | GTBT-36              | GTBT-48              | GTBT-60              |
| Power supply                         |                      | V-ph-Hz | 220-240-1-50                            | 220-240-1-50         | 380-420-3-50         | 380-420-3-50         |
| Cooling                              | Capacity             | Btu/h   | 24000                                   | 36000                | 48000                | 60000                |
|                                      | Input                | W       | 2620                                    | 3900                 | 5170                 | 6440                 |
|                                      | EER                  | W/W     | 2.68                                    | 2.7                  | 2.72                 | 2.73                 |
| Indoor fan motor                     | Model                |         | YSK74-4P                                | YSK140-4P            | YSK170-4P            | YSK180-4P            |
|                                      | Qty                  |         | 1                                       | 1                    | 1                    | 1                    |
|                                      | Speed (Hi/Med/Lo)    | r/min   | 1000/750/680                            | 1070/790/710         | 1070/750/650         | 1080/830/710         |
| Indoor air flow                      |                      | m3/h    | 1400/1100/1000                          | 2270/1890/1650       | 3010/2410/1940       | 3150/2510/1990       |
| Indoor external static pressure      |                      | pa      | 70                                      | 80                   | 100                  | 100                  |
| Indoor noise level (Hi/Med/Lo)       |                      | dB(A)   | 44/33/29                                | 49/39/36             | 49/39/36             | 50/42/37             |
| Indoor unit                          | Dimension (WxDxH)    | mm      | 920x635x270                             | 1140x775x270         | 1200x865x300         | 1200x865x300         |
|                                      | Net/Gross weight     | kg      | 28/33                                   | 42/46                | 48/56                | 48/56                |
| Outdoor fan motor                    | Model                |         | YDK53-6C                                | YDK75-6C             | YDK65-6F(B)          | YDK65-6F(B)          |
|                                      | Qty                  |         | 1                                       | 1                    | 2                    | 2                    |
|                                      | Speed                | r/min   | 800                                     | 860                  | 765                  | 765                  |
| Compressor                           | Туре                 | rotary  | scroll                                  | scroll               | scroll               | scroll               |
|                                      | Refrigerant          | R22     | R22                                     | R22                  | R22                  | R22                  |
| Outdoor air flow (Max.)              |                      |         | 2700                                    | 4200                 | 6200                 | 6500                 |
| Outdoor noise level (sound pressure) |                      |         | 58                                      | 58                   | 61                   | 62                   |
| Outdoor unit                         | Dimension (WxDxH)    | mm      | 845x320x700                             | 900x315x860          | 900x350x1170         | 900x350x1170         |
|                                      | Net/Gross weight     | kg      | 49/51                                   | 84/89                | 91.5/103             | 96/107               |
| Refrigerant piping                   | Liquid side/Gas side | mm      | \$\$\Phi_9.52\$\Phi_15.9\$(3/8^*/5/8^*) | @9.52/@19(3/8"/3/4") | Φ9.52/Φ19(3/8"/3/4") | Φ9.52/Φ19(3/8"/3/4") |
| Controller                           |                      |         | KJR-10B/DP(T)-E                         | KJR-10B/DP(T)-E      | KJR-10B/DP(T)-E      | KJR-10B/DP(T)-E      |
| Ambient temperature                  | e                    | °C      | 18-52                                   | 18-52                | 18-52                | 18-52                |





TEL: +971 6 5431127 / 06 5420603 FAX: 06 5432245, SHOWROOM TEL: 06 5423377, FAX: 06 5423366 E-mail: info@geogroupglobal.com, www.geogroupglobal.com