



CROSS-FLOW TYPE AIR CURTAIN





 Ambient flow without heating

 Metal casing, strong fire resistance, simple installation and easy cleaning.

 Double air way deflectors's design obtains an even air stream.

 The air wheel made of high-strength fiberglass plastic material, and the air wheel made of quality aluminum alloy, are especially suitable for the application of heavy oily smoke.

 Quality motor works for 5000 hours continuously without any defects.

 Multiple unit specifications: 900mm, 1000mm, 1200mm, 1500mm, 1800mm, 2000mm

Electrical Ratings

Model No.	Specification (mm)	Voltage / Frequency / Phase	Installation Height (m)	Power (W)		Air Speed (m/s)		Air Volume (m ³ /h)	Noise (dB)	Unit Size (mm)	Net Weight (kg)
				Low	High	Low	High				
FM3009-Y-2-S FM3009-Y-2-L	900	220V -/ 50Hz / 1Ph	2.3~3.0	115	166	9	11	1220	57	900 x 221 x 183	12.7
FM3010-Y-2-S FM3010-Y-2-L	1000			133	190			1450	58	1000 x 221 x 183	13.5
FM3012-Y-2-S FM3012-Y-2-L	1200			155	209			1710	59	1200 x 221 x 183	16.2
FM3015-Y-2-S FM3015-Y-2-L	1500			202	266			2230	60	1500 x 221 x 183	19.3